



Coaxial Dummy Load

中電力ダミーロード

特に1GHzまでのVSWR特性が良好なターミネーションで、組込用に適しています。



| 形式 | 周波数範囲 (GHz) | VSWR | 許容電力 (W) | 入力接栓 | 外形寸法 (W×H×L) |
|--|---|--|--|-------|---|
| DL-NP-05 DL-NP-10 DL-NP-20 DL-NP-30 DL-NP-50 DL-NP-100 | 0~4 | 1.2 1.2 1.2 1.2 1.2 1.3 | 5 10 20 30 50 100 | N-P | φ 25 × 46.5mm φ 40 × 54mm φ 40 × 76.5mm φ 50 × 101.5mm 59 × 69 × 72mm 66 × 89 × 182mm |
| DL-SMP-03 DL-SMP-05 DL-SMP-10 DL-SMP-20 | 0~12 | 1.3 | 3 5 10 20 | SMA-P | φ 13 × 30mm φ 22 × 31mm φ 35 × 44mm φ 40 × 65mm |
| DL-SMP-30 DL-SMP-50 DL-SMP-100 | 0~4 | 1.2 1.2 1.3 | 30 50 100 | SMA-P | φ 40 × 72mm 59 × 69 × 71mm 66 × 89 × 180mm |
| DL-30RD-NJ DL-50RD-NJ DL-101D-NJ DL-151D-NJ DL-201D-NJ DL-301D-NJ DL-301D-NJ-A DL-301DV2-NJ DL-501D-NJ DL-501D-NJ-A | 0~1 0~1 0~1 0~1 0~1 0~1 0~1 0~0.33 0~1 0~1 | 1.1 1.1 1.1 1.1 1.1 1.2 1.1 1.1 1.2 1.1 | 25 50 100 150 200 300 300 300 500 500 | N-J | 40 × 80 × 130mm 40 × 125 × 130mm 100 × 160 × 180mm 100 × 160 × 180mm 130 × 152 × 180mm 184 × 182 × 167mm 144 × 170 × 359mm 184 × 162 × 182mm 208 × 180 × 319mm 183 × 210 × 373mm |

共通規格 インピーダンス:50Ω

※入力接栓サイズや許容電力、周波数範囲は他にもありますので、ご相談ください。

